

1 ABSTRACT

2 A resonant optical filter including a first and second transmission optical waveguides,
3 and a resonator, which resonator may include one or more resonator segments evanescently
4 optically coupled therebetween. The resonator supports a circumferential resonant optical mode
5 and is evanescently coupled to each of the first and second transmission optical waveguides. In a
6 preferred embodiment, an optical signal entering the resonant optical filter through the first
7 transmission optical waveguide and substantially resonant with an optical resonance of the
8 resonator is substantially transferred to the second transmission optical waveguide and leaves the
9 resonant optical filter through the second transmission optical waveguide, while an optical signal
10 entering the resonant optical filter through the first transmission optical waveguide and
11 substantially non-resonant with an optical resonance of the coupled-optical-resonator system
12 substantially remains in the first transmission optical waveguide and leaves the resonant optical
13 filter through the first transmission optical waveguide. Where a resonator includes multiple
14 resonator segments, the resonator segments of the preferred embodiments are on the same optical
15 fiber and positioned sufficiently close together to enable optical coupling between them so as to
16 provide a tailored frequency filter function for optically coupling first and second transmission
17 optical waveguides. The resonators may be further provided with one or more alignment
18 structures including flanges and/or grooves for enabling passive positioning and/or supporting
19 first and second transmission optical waveguides including optical fibers and optical fiber tapers.
20 Structures may also be provided for suppressing undesired optical modes and/or resonances
21 associated with the resonators and/or alignment structures on the optical fiber.